



ZRP 60L Barrel pump

Fasspumpe 60L

Functional description

The ATN barrel pump is used to convey material out of barrels and hobbicks to the place of use. A scoop piston underpump conveys the material with an up and down stroke. A follower plate is pressed onto the material in the barrel so that the scoop piston underpump can reach it and convey it out of the barrel. It is possible to heat separate zones or the whole system for a more material friendly transport.

Product characteristics

- ✓ Conveying of adhesives, Sealing materials, filling materials out of 60l containers
- ✓ Conveying of low to high viscosity materials, abrasive and aggressive materials
- ✓ Assembly of different single components as a standard configuration or customer specific version
- ✓ Available as a heated or unheated version
- ✓ Usable as a Stand Alone Version (Supply cabinet included in scope of delivery)
- ✓ Different sizes and configurations possible



General technical data

Dimensions (WxDxH)	820 mm x 575 mm x 1735 mm (extended 1840 mm)	
Dimension	unheated:	507 mm x 380 mm x 734 mm
supply cabinet (WxDxH)	heated:	460 mm x 385 mm x 935 mm
Mass (without container)	240 kg	
Diameter		
follower plate	350 mm	
Two-hand operation	Yes	
Operating voltage	230/400 V 3xAC; 24DC	
Voltage level	400 V	
Max. backup fuse	20 A	
Max. temperature	heatable up to 100 °C	
Air supply	5 – 8 bar	
Noise emission	< 78 dB	
Material connection	G 3/4"	
Air connection (pneumatic)	Hose diameter 12 mm	
Housing material	SS	
Max. pump pressure	360 bar	
RAM pressure	7,3 kN	

Delivery volume scoop piston underpump

At 30 double strokes/min

• SUP 80	2,4 l/min / 80 cm ³ per double stroke
• SUP 150	4,5 l/min / 150 cm ³ per double stroke
• SUP 260	7,8 l/min / 260 cm ³ per double stroke

Ratio of scoop piston underpump / air motors

Medium pump	Delivery volume per double stroke	Air motors			
		LMR 125	LMR 160	LMR 250	LMR 320
SUP 80	80 cm ³	35:1	57:1	-	-
SUP 150	150 cm ³	17:1	28:1	68:1	-
SUP 260	260 cm ³	11:1	18:1	44:1	72:1

The use and combination of pump and air motor depends on the material to be pumped and is done individually.

Applicable materials

PVC and other sealants

SMP-Adhesives

Silicones

Epoxy resins

Butyl rubbers

PU-Adhesives

Acrylates

Options and functional extensions

Residual quantity-optimized follower plate

Extension to a double barrel pump

Dosing controls

Signal tower „Active“, „Ready“, „Empty“

Operating extension to IFC 10

Stand Alone version with supply cabinet

Scoop piston underpump in stainless steel available

Encapsulation possible for temperatures > 100 °C